

# 8400 Series

# Tubeaxial

## 80x80x25mm



■ DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.

■ With electronic protection against reverse polarity, blocking and overloading; partially impedance protected.

■ Mounting from either face using four 4.3 mm holes.

■ Fan of fiberglass reinforced plastic. PBTP housing, PA impeller.

■ Air exhaust over struts. Rotational direction CCW looking at rotor.

■ Electrical connection via 2 leads AWG 24, TR 64. Stripped and tinned ends.

■ UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	CFM @ 0	Curve	Volts	Voltage Range	Power (W)	dBA	Max Ambient Temp C	Wgt. (lbs)	Type Of Bearing	Features
8412GL	21	1	12	7 to 15	0.8	20	75	0.31	Sintec	Leads
8412L	21	1	12	7 to 15	0.8	21	75	0.31	Ball	Leads
8412GM	27	2	12	7 to 15	1.2	29	75	0.31	Sintec	Leads
8412M	27	2	12	7 to 15	1.4	29	75	0.31	Ball	Leads
8412	33	3	12	7 to 15	2.4	35	75	0.31	Ball	Leads
8412/12	33	3	12	7 to 15	2.4	35	75	0.31	Ball	Leads
8412/2	33	3	12	7 to 15	2.4	35	75	0.31	Ball	Leads
8412G	33	3	12	7 to 15	2.3	35	75	0.31	Sintec	Leads
<hr/>										
8414GL	21	1	24	12 to 28	0.8	20	75	0.31	Sintec	Leads
8414L	21	1	24	12 to 28	0.8	21	75	0.31	Ball	Leads
8414GM	27	2	24	12 to 28	1.2	29	75	0.31	Sintec	Leads
8414M	27	2	24	12 to 28	1.4	29	75	0.31	Ball	Leads
8414	33	3	24	12 to 28	2.4	35	75	0.31	Ball	Leads
8414/2	33	3	24	12 to 28	2.4	35	75	0.31	Ball	Leads
8414G	33	3	24	12 to 28	2.3	35	75	0.31	Sintec	Leads

